

# SAFETY DATA SHEET

Issuing Date 06-Jun-2017

Revision Date 23-Jan-2019

**Revision Number** 2



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

# 1. IDENTIFICATION

Product identifier

Product Name E.S. 829

Other means of identification

(M)SDS Number 1347573

Recommended use of the chemical and restrictions on use

**Recommended Use** For industrial use only

Uses advised against No information available

Details of the supplier of the safety data sheet

**Supplier Identification** 

Address CEDA Specialty Services LP

2130-121 Ave. NE

Edmonton, Alberta T6S 1B1

Canada

Telephone (780) 472-6766

E-mail info@cedagroup.com

# 2. HAZARDS IDENTIFICATION

### Classification

| Skin corrosion/irritation                          | Category 1 Sub-category C |
|--|---------------------------|
| Serious eye damage/eye irritation                  | Category 1                |
| Carcinogenicity                                    | Category 1A               |
| Specific target organ toxicity (repeated exposure) | Category 1                |

**(II)** 

**Appearance** Brown

Physical state Bonded, fibrous glass web

**Odor** Pungent

### GHS Label elements, including precautionary statements

#### **Danger**

#### **Hazard statements**

Causes severe skin burns and eye damage May cause cancer Causes damage to organs through prolonged or repeated exposure



### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Wear protective gloves/protective clothing/eye protection/face protection Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

### **Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor

Specific treatment (see supplemental first aid instructions on this label)

#### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor

# Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

Wash contaminated clothing before reuse

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing

Immediately call a POISON CENTER or doctor

### Ingestion

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting

#### **Precautionary Statements - Storage**

Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Other information

May be harmful if swallowed

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Substance



Not applicable.

#### Mixture

| Chemical Name             | CAS-No      | Weight-% | Hazardous Material<br>Information Review Act<br>registry number (HMIRA<br>registry #) | Date HMIRA filed and date exemption granted (if applicable) |
|---------------------------|-------------|----------|---|---|
| Hydrous Alum Silicates    | 1332-58-7   | 45-50    | -   | -   |
| Proprietary Resin         | -           | 20-25    | -   | -   |
| Sodium silicate           | 1344-09-8   | 5-10     | -   | -   |
| Refractory ceramic fibers | 142844-00-6 | 3-8      | -   | -   |
| Quartz                    | 14808-60-7  | 1-5      | -   | -   |
| Cellulose                 | 9004-34-6   | 1-5      | -   | -   |

### 4. FIRST AID MEASURES

First aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance. IF exposed or concerned: Get medical advice/attention.

**Inhalation** Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate medical

advice/attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and

easy to do. Continue rinsing. Get immediate medical advice/attention.

**Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Get immediate medical advice/attention.

**Ingestion** Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Get immediate medical

advice/attention.

**Self-protection of the first aider** Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

**Symptoms** Burning sensation.

Indication of any immediate medical attention and special treatment needed

**Note to physicians** Product is a corrosive material. Use of gastric lavage or emesis is contraindicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood

pressure may occur with moist rales, frothy sputum, and high pulse pressure.

# 5. FIRE-FIGHTING MEASURES



Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the

chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition

can lead to release of irritating gases and vapors.

Hazardous Combustion Products Carbon oxides.

**Explosion Data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

# 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Personal precautions Attention! Corrosive material. Avoid contact with skin, eyes or clothing. Ensure adequate

ventilation. Use personal protective equipment as required. Evacuate personnel to safe

areas. Keep people away from and upwind of spill/leak.

**Other Information** Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated

clothing and wash before reuse.

# Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other

materials.



- E.S. 829 Revision Date 23-Jan-2019

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Limits .

| Chemical Name          |      | ACGIH T                               | LV            | 09                                  | SHA PEL                    |                              | NIOSH      | HIDLH                     |
|------------------------|------|---------------------------------------|---------------|-------------------------------------|----------------------------|------------------------------|------------|---------------------------|
| Hydrous Alum Silicate  | es   | TWA: 2 mg/m³ particulate              |               | TWA: 15                             | mg/m³ total dust           | TWA                          | A: 10 mg/i | m <sup>3</sup> total dust |
| 1332-58-7              |      | matter containing                     | no asbestos   | TWA: 5 m                            | ng/m³ respirable           | TWA:                         | 5 mg/m³    | respirable dust           |
|                        |      | and <1% crystal                       | lline silica, | 1                                   | fraction                   |                              |            |                           |
|                        |      | respirable particu                    | ılate matter  | (vacated) TV                        | NA: 10 mg/m³ total         |                              |            |                           |
|                        |      |                                       |               |                                     | dust                       |                              |            |                           |
|                        |      |                                       |               |                                     | ) TWA: 5 mg/m <sup>3</sup> |                              |            |                           |
|                        |      |                                       |               |                                     | rable fraction             |                              |            |                           |
| Quartz                 |      | TWA: 0.025 mg/m                       |               | TWA: 0.1                            | mg/m³ (vacated)            |                              |            | respirable dust           |
| 14808-60-7             |      | fraction                              | 1             |                                     |                            | IWA                          | . ~        | g/m³ respirable           |
|                        |      |                                       |               |                                     |                            | dust                         |            |                           |
| Cellulose              |      | TWA: 10 mg/m <sup>3</sup>             |               | TWA: 15 mg/m³ total dust            |                            | TWA: 10 mg/m³ total dust     |            |                           |
| 9004-34-6              |      |                                       |               | TWA: 5 mg/m <sup>3</sup> respirable |                            | TWA: 5 mg/m³ respirable dust |            |                           |
|                        |      |                                       | fraction      |                                     |                            |                              |            |                           |
|                        |      |                                       |               | (vacated) TWA: 15 mg/m³ total       |                            |                              |            |                           |
|                        |      |                                       |               | (vacated                            | ) TWA: 5 mg/m <sup>3</sup> |                              |            |                           |
|                        |      |                                       |               | ,                                   | rable fraction             |                              |            |                           |
| Chemical Name          |      | Alberta                               | British C     | Columbia                            | Ontario TWAE               | V                            | (          | Quebec                    |
| Hydrous Alum Silicates | 7    |                                       |               | 2 mg/m <sup>3</sup>                 | TWA: 2 mg/m                |                              |            | A: 5 mg/m <sup>3</sup>    |
| 1332-58-7              |      | TVVA. 2 mg/m²                         |               | - 111g/111                          | 1 vv/\. 2 mg/m             |                              | 1 007      | t. 5 mg/m                 |
| Quartz                 | TW   | VA: 0.025 mg/m <sup>3</sup> TWA: 0.02 |               | 025 mg/m <sup>3</sup> TWA: 0.10 mg/ |                            | m³                           | TWA        | : 0.1 mg/m <sup>3</sup>   |
| 14808-60-7             |      |                                       |               | -                                   |                            |                              |            | -                         |
| Cellulose              | TWA: | 10 mg/m <sup>3</sup> TWA: 5           | TWA: 1        | 0 mg/m³                             | TWA: 10 mg/m               | 1 <sup>3</sup>               | TWA: 10    | mg/m³ TWA: 5              |
| 9004-34-6              |      | mg/m³                                 | TWA: 3        | 3 mg/m <sup>3</sup>                 |                            |                              |            | mg/m³                     |

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Face protection shield. Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves. Impervious gloves. Viton™. Neoprene gloves. Nitrile rubber.

**Skin and body protection** Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

**General hygiene considerations** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do

not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Handle in accordance with good industrial hygiene and safety practice.



# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state Bonded, fibrous glass web

Appearance Brown Odor Pungent

Color No information available
Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>

pH10.7None knownMelting / freezing pointNo data availableNone knownBoiling point / boiling rangeNo data availableNone known

Flash Point 180 Cleveland Open Cup (COC)

Evaporation RateNo data availableNone knownFlammability (solid, gas)No data availableNone known

Flammability Limit in Air None known

Upper flammability limit No data available
Lower flammability limit No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone knownRelative density1.61None known

Water Solubility Insoluble in water

Solubility(ies) No data available None known

Partition coefficient: n-octanol/water Not Applicable

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone knownKinematic viscosityNo data availableNone knownDynamic viscosityNo data availableNone known

**Explosive properties**No information available **Oxidizing properties**No information available

Other Information

Softening Point
Molecular Weight
VOC Content (%)
Liquid Density
Bulk Density
Particle Size
Particle Size
No information available

# 10. STABILITY AND REACTIVITY

Reactivity No information available. Chemical

**stability** Stable under normal conditions.

Possibility of Hazardous Reactions 
None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Conditions to avoid** Exposure to air or moisture over prolonged periods.

Incompatible materials Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products Carbon oxides.



# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs.

Pulmonary edema can be fatal.

Eye contact Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Corrosive to the eyes and may cause severe damage including blindness.

Causes serious eye damage. May cause irreversible damage to eyes.

**Skin contact** Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Prolonged skin contact causes burns. Symptoms may be delayed.

**Ingestion** Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung

damage if swallowed. May be fatal if swallowed and enters airways.

### Information on toxicological effects

**Symptoms** Redness. Burning. May cause blindness. Coughing and/ or wheezing.

### Numerical measures of toxicity

### **Acute Toxicity**

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 4,544.00 mg/kg

Unknown acute toxicity
Component Information

No information available

| Chemical Name          | LD50 Oral          | LD50 Dermal           | Inhalation LC50        |  |
|------------------------|--------------------|-----------------------|------------------------|--|
| Hydrous Alum Silicates | > 5000 mg/kg (Rat) | > 5000 mg/kg (Rat)    |                        |  |
| Sodium silicate        | = 1960 mg/kg (Rat) | > 4640 mg/kg (Rabbit) |                        |  |
| Cellulose              | > 5 g/kg (Rat)     | > 2 g/kg (Rabbit)     | > 5800 mg/m³ (Rat) 4 h |  |

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Prolonged skin contact causes burns.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Risk of serious

damage to eyes.

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

Carcinogenicity Classification based on data available for ingredients. Contains a known or suspected

carcinogen.



The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Chemical Name          | ACGIH | IARC     | NTP                    | OSHA |
|------------------------|-------|----------|------------------------|------|
| Hydrous Alum Silicates | A2    | Group 2B | Reasonably Anticipated | X    |
| 1332-58-7              |       | -        |                        |      |
| Quartz                 | A2    | Group 1  | Known                  | X    |
| 14808-60-7             |       | •        |                        |      |

### Legend

**ACGIH (American Conference of Governmental Industrial Hygienists)** 

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure**Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** No information available.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity** The environmental impact of this product has not been fully investigated.

| Chemical Name   | Toxicity to Algae | Toxicity to Fish                                 | Toxicity to Microorganisms | Daphnia Magna (Water<br>Flea) |
|-----------------|-------------------|--|----------------------------|-------------------------------|
| Sodium silicate |                   | 96h LC50: = 3185 mg/L<br>(Brachydanio rerio) 96h | -                          | 96h EC50: = 216 mg/L          |
|                 |                   | LC50: 301 - 478 mg/L                             |                            |                               |
|                 |                   | (Lepomis macrochirus)                            |                            |                               |

Persistence and Degradability No information available.

**Bioaccumulation** There is no data for this product.

Mobility No information available.

Other adverse effects No information available.

### 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

**Contaminated packaging** Do not reuse empty containers.



- **E.S. 829** Revision Date 23-Jan-2019

# 14. TRANSPORT INFORMATION

**DOT** NOT REGULATED

TDG Not regulated

MEX NOT REGULATED

ICAO NOT REGULATED

IATA Not regulated

IMDG Not regulated

RID NOT REGULATED

ADR NOT REGULATED

ADN NOT REGULATED

### 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

**Export Notification requirements** Not applicable

**International Inventories** 

TSCA Complies.
DSL/NDSL Complies.
EINECS/ELINCS Complies.

ENCSContact supplier for inventory compliance status.KECLContact supplier for inventory compliance status.PICCSContact supplier for inventory compliance status.

AICS Complies.

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372



Acute Health HazardYesChronic Health HazardYesFire HazardNoSudden release of pressure hazardNoReactive HazardNo

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

### US State Regulations

### **California Proposition 65**

This product contains the following Proposition 65 chemicals.

| Chemical Name                           | California Proposition 65                                     |
|---|---|
| Refractory ceramic fibers - 142844-00-6 | carcinogen, 7/1/1990 (airborne particles of respirable size)  |
| Quartz - 14808-60-7                     | carcinogen, 10/1/1988 (airborne particles of respirable size) |

### U.S. State Right-to-Know Regulations

This product may contain substances regulated by state right-to-know regulations.

| Chemical Name          | New Jersey | Massachusett | Pennsylvania | Rhode Island | Illinois |
|------------------------|------------|--------------|--------------|--------------|----------|
|                        |            | S            |              |              |          |
| Hydrous Alum Silicates | Х          | Х            | X            |              |          |
| 1332-58-7              |            |              |              |              |          |
| Quartz                 | Х          | Х            | Х            |              | Х        |
| 14808-60-7             |            |              |              |              |          |
| Cellulose              | Х          | Х            | Х            | -            | Х        |
| 9004-34-6              |            |              |              |              |          |

# **16. OTHER INFORMATION**

NFPA Health hazards 3 Flammability 1 Instability 0 Physical and Chemical Properties -

HMIS Health hazards 3 \* Flammability 1 Physical hazards 0 Personal Protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Prepared By
Product Stewardship
23 British American Blvd.

Latham, NY 12110 1-800-572-6501

**Issuing Date** 06-Jun-2017

Revision Date 23-Jan-2019

Revision Note No information available

Disclaimer



- **E.S. 829** Revision Date 23-Jan-2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**